

# D8x12 NAVIGATOR® HORIZONTAL DIRECTIONAL DRILL



**STRAIGHTFORWARD CONTROLS.** Controls with minimal electrical components, bringing you back to the basics with modern technology.



**NARROW FOOTPRINT.** This drill is 8.5" (21.6 cm) narrower in width than the next sized drill in the lineup and can get through a 36" (91.4 cm) gate or fit on a narrow trailer with other jobsite essentials.



**LOW SOUND LEVELS.** Low noise emission levels at the operator's ear of 85 dBA and a guaranteed sound power of 104 dBA make this drill perfect for installing small utilities in an urban environment with minimal disruption.



**MORE POWER.** Equipped with a 48 hp (35.8 kW) Kohler engine, this drill offers 1200 ft-lb (1627 Nm) of spindle torque and 7850 lb (3563.9 kg) of thrust/pullback.



**TRACKS.** Tracks offer ideal traction for operation while providing minimal ground disturbance. This track system design allows a forward ground drive speed of 2.8 mph (4.5 km/h), which is 45% faster than the leading competitor.



**MULTIPLE ROD OPTIONS.** Equip your drill with either a 6' (1.8 m), 1.66" or 1.31" (4.2 cm or 3.3 cm) Firestick® drill rod and save time on the job with 180' (54.9 m) of on-machine rod carrying capacity.

# D8x12 NAVIGATOR® HORIZONTAL DIRECTIONAL DRILL

## GENERAL WEIGHTS AND DIMENSIONS

Min transport length: 139" (353.1 cm)

Min transport width: 35.5" (90.2 cm)

Min transport height: 65" (165.1 cm)

Min weight: 6000 lb (2721.6 cm)

Max weight: 6600 lb (2993.7 cm)

Angle of approach: 18 deg

Angle of departure: 20 deg

## ENGINE

Make and model: Kohler KDI1903

Fuel type: Ultra-low sulfur diesel

Max engine rpm: 2200 rpm

Gross horsepower: 48 hp (35.8 kW)

Aspiration at full engine load: Turbocharged

Max fuel consumption: 2.5 gph (9.4 lph)

Emissions rating: Tier 4 Final (Stage IV)

Max operating angle (fore/aft): 25 deg

Max operating angle (left/right): 25 deg

## OPERATIONAL

Thrust rod: 7850 lb (3563.9 kg)

Pullback rod: 7850 lb (3563.9 kg)

Max carriage speed at max engine rpm - fpm (m/min): 159 fpm  
(48.5 m/min)

Max spindle torque (max engine rpm) - ft-lb (Nm): 1200 ft-lb  
(1627 Nm)

Max spindle torque - smaller rod option (max engine rpm) - ft-lb  
(Nm): 900 ft-lb (1220 Nm)

Max spindle speed at max engine rpm - (rpm): 182 rpm

Min bore diameter: 2.5" (6.4 cm)

Max ground drive speed at max engine rpm - mph: 2.8 mph  
(4.5 km/h)

Noise level at operator's ear: 85 dB(A)

Guaranteed sound power engine: 104 dB(A)

## FLUID CAPACITIES

Fuel tank: 15 gal (56.7 L)

Hydraulic system: 25 gal (94.6 L)

## DRILLING FLUID SYSTEM

Max flow: 9 gpm (34.1 L/min)

Max pressure: 750 psi (50.2 bar)

Brand: FMC

Onboard tank capacity: 25 gal

## FEATURES

Breakout system: Standard hydraulic vise

Drilling lights: Optional

Stakedown system: Standard

Strike Alert: Standard

Remote Lockout Control: Standard

Rod greaser: Optional

Wash wand: Optional

## DRILL PIPE OPTION ONE

Thread type: Firestick drill rod (#200)

Length: 6" (1.8 m)

Rod diameter: 1.31" (3.3 cm)

Joint inside diameter: .8" (2 cm)

Joint outside diameter: 1.88" (4.8 cm)

Weight: 18 lb (8.2 kg)

Bend radius: 57' (17.4 m)

Total machine rod capacity: 180' (54.9 m)

## DRILL PIPE OPTION TWO

Thread type: Firestick drill rod (#200)

Length: 6' (1.8 m)

Rod diameter: 1.66" (4.2 cm)

Joint inside diameter: .8" (2 cm)

Joint outside diameter: 1.88" (4.8 cm)

Weight: 26 lb (11.8 kg)

Bend radius: 95.5' (29.1 m)

Total machine rod capacity: 180' (54.9 m)

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Firestick and Navigator are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Kohler is a trademark of Kohler Co. © 2018 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

